



## WATERPROOF IP69K WASHDOWN BARLIGHTS

FOR FOOD, BEVERAGE & PHARMACEUTICAL MACHINE VISION APPLICATIONS:

Pick & Place robotics

00,00

- Product, packaging & label inspection
- Foreign object detection

- Manufacturing Process Control
- Aseptic manufacturing

IP69K washdown lights provide HIGH BRIGHTNESS, UNIFORM ILLUMINATION in a reliable package designed to withstand the rigours of harsh chemical cleaning & de-contamination.

- Smooth cylindrical surfaces for RAPID CLEANING
- ✓ Wide range of **CLEANING SOLVENTS**
- Suitable for **HIGH HUMIDITY** environments
- ✓ Wide ambient **OPERATING TEMPERATURE** range
- ✓ LONGEST BARS on the market up to 1250mm
- Swivel mounting brackets for EASY INSTALLATION
  - 6 COLOUR OPTIONS covering most applications
- Simple, PLUG & LIGHT 24VDC operation
- Integrated CURRENT CONTROLLER & single M12 connection

✓ 3 YEAR WARRANTY\* ✓ SHORT LEAD-TIME

WATERPROOF

P69K



#### IP69K WASHDOWN LIGHTS

are so much more than a light in a waterproof casing! Read our Tech Note to understand **WHY** you may need a **TPL Vision IP69K Washdown light**.


#### LIGHTING METHODS



#### SUITABLE FOR HARSH FOOD & CHEMICAL ENVIRONMENTS.


Backlight version available: see **Waterproof IP69K Washdown Backlight Bars**.

### LIGHTING AREA



#### **TECHNICAL DATA** Operating voltage 24 VDC Supplied cable length 5 meters Continuous and Strobe Operating modes PNP & NPN Trigger (strobe) mode Rise time / Fall time 15 µs / 10 µs Yes, 100% - 35% Dimming control 20°C to +60°C (-4°F to +140°F)\* Ambient temperature Ambient humidity 80% max IP69K (IEC 60529) IP rating Housing 316L stainless steel / food grade PPMA L-Brackets (included) Design permits 360° rotation of light 3 years (UV: 1 year) Warrantv See www.tpl-vision.com/warranty **COLOURS:** WHI 470 525 630 IR 850 UV 405 **DIFFUSER OPTIONS:** OPAQUE SATIN POLARISED

SIZE OPTIONS



\*\* See Technical User Guide



#### REFERENCE BUILDER

EBAR –	LENGTH (cm)	WAVELENGTH (nm or WHI)		LENS TYPE	ENCLOSURE RATING	DIFFUSER AND POLARISER OPTION
	125	WHI	7	(±7°)	IP69K	DO (opaque)
	250	405	10	(±10°)		DS (satin)
	375	470	9-16	(±9-16°)		POL (polariser)
	500	525	17	(±17°)		(leave blank for clear window)
	625	630	25	(±25°)		Note: cannot be fitted retro- spectively, must be specified
	750	850	NL	(no lens)	at time of order.	
	875					Polariser not suitable for use with 850nm (IR) option.
	1000	EXAMPLES: • EBAR+ IP69K 125mm white LED ±7° lenses transparent diffuser → EBAR-125-WHI-7-IP69K • EBAR+ IP69K 500mm green LED ±17° lenses opaque diffuser → EBAR-500-525-17-IP69K-D0				
	1125					
	1250					



\*TPL Vision is a true partner. TPL provides outstanding service and support. We have found their responsiveness to be unmatched in the industry.??

Jeff Youngs, President and CEO, ProSpection Solutions, LLC



# www.**tpl-vision**.com

TPL VISION IS AN **ISO9001** CERTIFIED MANUFACTURER

Features and presentations liable to modifications without prior notice.