

BAR RANGE

RING

DOME

LOW ANGLE

SPOT

BACKLIGHT

MODULAR

OVERDRIVE x4
MODULAR M-EBAR

OVERDRIVE x4.5
MODULAR M-TBAR

OVERDRIVE x4
MODULAR RINGLIGHT

OVERDRIVE x4
MR - DOME

OVERDRIVE x4
MR - LOW ANGLE

STANDARD

EBAR+

BLBAR+

HPRING

HPFDOME

LOW ANGLE II

TSPOT 1

HPBACK

SBACK II

EBAR+ UV 365, 385 & 405

XBAR RGB

TRING

SDOME II

TSPOT 4

Bn'L (Black & Light)

LED BRICK

LINK

EBAR+ LINK

BLBAR+ LINK

LDOME

NEW
FLUORESCENCE IMAGING SOLUTION

SBAR

SBAR UV 365, 385 & 405

Collimated CMBACK+

Collimated CSBACK

OVERDRIVE

OVERDRIVE x4
EBAR+ OVERDRIVE

OVERDRIVE x4
BLBAR+ OVERDRIVE

OVERDRIVE x3
MFDOME+ OVERDRIVE

OVERDRIVE x3
ZOOM Z-SPOT

OVERDRIVE x3
MBACK+ OVERDRIVE

OVERDRIVE x3
Collimated CMBACK+ OVERDRIVE

OVERDRIVE IN-BUILT
EBAR LOGISTIX

OVERDRIVE IN-BUILT
FLOOD LIGHT

OVERDRIVE x3
Bn'L (Black & Light) OVERDRIVE

* Other colours: please contact us.

IP69K

DEDICATED TO FOOD INDUSTRY
IP69K BARLIGHT

DEDICATED TO FOOD INDUSTRY
IP69K BACKLIGHT BAR

ADD-ONS

AC-TBAR

AC-EBAR

DIFFUSERS & POL

FILTERS

MOUNTING

CABLES

LEGEND

- White WHI
- White-Infrared
- Red 630nm
- Red-Cyan
- Green 525nm
- 365 Ultraviolet 365nm
- Blue 470nm
- 385 Ultraviolet 385nm
- Infrared
- 395 Ultraviolet 395nm
- RGB
- 405 Ultraviolet 405nm
- 65 IP65 by default
- 66 IP66 by default
- 67 IP67 by default
- 69K IP69K by default
- 65 Optional: IP65
- 66 Optional: IP66
- 69K Optional: IP69K