

GAMME BAR

RING

DOME

LOW ANGLE

SPOT

BACKLIGHT

MODULAR

OVERDRIVE x4  
MODULAR M-EBAR

OVERDRIVE x4.5  
MODULAR M-TBAR

OVERDRIVE x4  
MODULAR RINGLIGHT

OVERDRIVE x4  
MR - DOME

OVERDRIVE x4  
MR - LOW ANGLE

STANDARD

EBAR+

BLBAR+

HPRING

HPFDOME

LOW ANGLE II

TSPOT 1

HPBACK

SBACK II

EBAR+ UV 365, 385 & 405

XBAR RGB

TRING

SDOME II

TSPOT 4

Bn'L (Black & Light)

LED BRICK

LINK

EBAR+ LINK

BLBAR+ LINK

LDOME

FLUORESCENCE IMAGING SOLUTION

SBAR

SBAR UV 365, 385 & 405

Collimated CMBACK+

Collimated CSBACK

OVERDRIVE

OVERDRIVE x4  
EBAR+ OVERDRIVE

OVERDRIVE x4  
BLBAR+ OVERDRIVE

OVERDRIVE x3  
MFDOME+ OVERDRIVE

OVERDRIVE x3  
ZOOM Z-SPOT

OVERDRIVE x3  
MBACK+ OVERDRIVE

OVERDRIVE x3  
Collimated CMBACK+ OVERDRIVE

OVERDRIVE INTEGRE  
EBAR LOGISTIX

OVERDRIVE INTEGRE  
FLOOD LIGHT

OVERDRIVE x3  
Bn'L (Black & Light) OVERDRIVE

\* Autres couleurs : nous contacter.

IP69K

SPECIAL AGRO-ALIMENTAIRE  
ÉCLAIRAGE DIRECT IP69K

SPECIAL AGRO-ALIMENTAIRE  
ÉCLAIRAGE BACKLIGHT IP69K

ADD-ONS

AC-TBAR

AC-EBAR

DIFFUSANTS & POL.

FILTRES

FIXATIONS

CÂBLES

LÉGENDE

- Blanc WHI
- Rouge 630nm
- Vert 525nm
- Bleu 470nm
- Infrarouge
- RGB
- Blanc-Infrarouge
- Rouge-Cyan
- 365 Ultraviolet 365nm
- 385 Ultraviolet 385nm
- 395 Ultraviolet 395nm
- 405 Ultraviolet 405nm
- 65 IP65 par défaut
- 66 IP66 par défaut
- 67 IP67 par défaut
- 69K IP69K par défaut
- 65 Option : IP65
- 66 Option : IP66
- 69K Option : IP69K