

SPEED SCONTROL

FAST STROBE - 1 CHANNEL



FEATURES

- fast strobe mode,
- current: 700 mA,
- no setting,
- casing ergonomic.

More information about the **Speed SCONTROL** :

www.tpl-vision.com

REFERENCE

Ref: **SCONTROL**

The **Speed SCONTROL** enables the power supply of lightings similar to ThinLED, in 700 mA with very short rising and falling times. It works only in strobe mode, and cannot be customised. Even with very short shooting times, the user can easily synchronise the lighting with the camera.

The strobe input being optocoupled, the triggering system is isolated from the rest of the internal electronics. As soon as there is a positive voltage between + Strobe and - Strobe, the **Speed SCONTROL** lights the led system. To gain additional speed, the regulation is made through linear regulators. The latter absorb excess energy, so as to offer the most relevant current/voltage ratio for the lighting. The **Speed SCONTROL** is protected against polarity reversal in inputs, so as to avoid any risk of destruction because of wrong connections.

Electronics	
Power supply	from 7 to 28 V
Output current	700 mA
Maximum rising time	10 µs
Maximum falling time	10 µs
Mechanics	
Dimensions	126 x 41 x 40 mm
Weight	88 g
Environment	
Operating temperature	0 - 40°C
Storage temperature	0 - 60°C
IP protection	IP 20
Labels	RoHS-CE-DEEE